



**DIMENSIONS**

LEAKAGE DISTANCE 1,387 mm  
 DRY ARCING DISTANCE 550 mm

SHEDS Q'TY 8 PCS

**MECHANICAL VALUES**

SPECIFIED CANTILEVER LOAD 11 kN  
 ROUTINE CANTILEVER LOAD 5.5 kN

**ELECTRICAL VALUES**

Low-Freq. FLASHOVER-DRY 230 kV  
 Low-Freq. FLASHOVER-WET 200 kV  
 IMPULSE FLASHOVER-POS 380 kV  
 IMPULSE FLASHOVER-NEG 470 kV

**PACKING INFORMATION**

NET WEIGHT EACH 14 kg  
 PACKED WEIGHT EACH 14.4 kg  
 NO. IN STANDARD PACKAGE 3 PCS

**NOTE:**

1. TIE TOP END FITTINGS ARE MADE FROM ALUMINUM ALLOY.
2. FIBERGLASS ROD IS MADE FROM EPOXY RESIN.
3. STUD BASE DIMENSIONS ARE IN ACCORDANCE WITH ANSI C29.7
4. THE DIA. OF FRP ROD IS 45mm SOLID.
5. BASE AND INSULATOR ASSEMBLED WITH M20 BOLT AND WASHER.

<small>THESE DRAWINGS AND SPECIFICATIONS, AND THE DATA CONTAINED THEREIN, ARE THE EXCLUSIVE PROPERTY OF DTR CORPORATION. THESE DRAWINGS ARE ISSUED IN STRICT CONFIDENCE AND SHALL NOT, WITHOUT THE PRIOR WRITTEN PERMISSION OF DTR CORPORATION, BE REPRODUCED, COPIED, OR USED FOR ANY PURPOSE WHATSOEVER, EXCEPT THE MANUFACTURE OF ARTICLES FOR DTR CORPORATION.</small>	DIMENSIONAL TOLERANCES UNLESS OTHERWISE NOTED X ±0.1 XX ±0.02 XXX ±0.010 ANGLES ±1°	Designed by C.H.PARK	Date 09/30/09	Part Number DTR-LPFN-69SK-NZI	Scale N/A
	<b>DTR</b>		<b>69kV LINE POST INSULATOR TIE TOP</b>		Filepath
			Units mm	Sheet 1/1	